

Super-Lube™

TB:SL01
Page 1 of 1
Revised 5/1/99

- DEFINITION:** **Super-Lube** is a lubricant for pelleting hard-to-pellet feeds. That is, those difficult to get through the die.
- MODE OF ACTION:** Heat and moisture in the conditioning chamber liquifies and activates **Super-Lube** thereby improving steam penetration into feed, coating the surface of the feed and reducing friction at the die.
- COMPOSITION:** Sodium salts of fatty acids, locust bean gum, and hydrogenated tallow glycerides.
- FEED TAG LABEL RECOMMENDATIONS:** We are citing the **FDA regulation 501.100 (3)(ii)(c), 21 CFR**, which exempts animal food processing aids from compliance with the required declaration on an animal feed label of ingredients. **Super-Lube** meets the established standard as *"substances that are added to a food for their technical or functional effect in the processing but are present in the finished food at insignificant levels and do not have any technical or functional effect in that food."*
- CARRIER:** None
- COLOR:** Off-white or cream
- ODOR:** Mild
- USE LEVEL:** 2 to 4 lbs. per ton of ration being pelleted. Normal use rate is 2 lb. per ton.
- PACKAGING:** 50 pound multi-wall, poly-lined paper bags.
- STORAGE:** **Super-Lube** stores well and remains stable under normal conditions. However, bag should be kept closed and stored in a cool, dry place.
- BULK DENSITY:** 30-32 lbs./cu. ft.